



Balance of Performance SRO GT4 CARS TRACKS C



BALANCE OF PERFORMANCE FOR SRO GT4 CARS:

TRACKS C: REDBULL RING

These balance of performance measures are the result of the tests, research, analysis and projections performed by SRO Ltd and are the sole property of SRO Ltd. Other series promoters, race organisers and national sporting authorities cannot use all or part of them without SRO Ltd's prior written consent. Any contravention will result in a legal action.



Balance of Performance SRO GT4 CARS TRACKS C



Make MAP	Model	Min Weight kg	BOP Ballast kg	Total weight	Ride Height Front	BOP extra mm	Ride Height Rear	BOP Extra mm	Comments
Aston Martin	Vantage AMR GT4	1445	+60	1505	93	+10	102	+0	SRO 2020 MAP 3 ECU MAP BOP 2020
Aston Martin	Vantage AMR GT4 EVO	1475	+30	1505	93	+10	102	+5	*MAP Restricted 2 ECU BOP 2024
Audi	R8 LMS GT4	1460	+15	1475	95	+10	107	+5	Restrictor 46 mm ECU BOP 2021
BMW	G82 M4 GT4	1480	+30	1510	138,90	+16,10	149,50	+10,50	MAP: 4 LT: +0 ECU BOP 10/2022
Mercedes	AMG GT4	1400	+50	1450	93	+10	96	+5	Power Level 3 MAP 2019 ECU BOP 2020
Porsche	718 Cayman GT4 RS Clubsport	1330	+65	1395	97	+5	100	+0	Restrictor 53,7 mm ECU BOP MAP 2022
Toyota	GR Supra GT4 EVO	1370	+30	1400	165	+10	165	+5	Silver Power Stick ECU BOP 2023

Remarks :

- Additional BOP Ballast must be installed according to the ADAC GT4 Technical Regulations
- ECU BOP maps are saved in the dataloggers for scrutineering.
- GT4 Cars are only eligible if presented with GT4 homologation file and SRO GT4 Certificate
- SRO GT Bureau can use any parameter for BOP purposes and can change the BOP of any car at any moment during the event.
- Engine reference data (iA, Lambda, Fuel inj, Cam In/Out, airbox pressure) is the one collected during BOP tests and will be used for checks. If noted differently in comments the (e.g. iA, Lambda, Fuel inj, Cam In/Out, airbox pressure) is set as reference.
- Turbo cars with adaptable Pboost have to apply ratio approach. Ratio (Pboost Map/1000mbar x Official Atmospheric Pressure)
- Turbo cars without adaptable pboost , identified by * in the BOP sheet, need to add +15 kg per 20 mbar ambient pressure delta under 1000mbar, this means + 15 kg at Patmo of 980mb, +30 kg at Patmo of 960 mbar, +45 kg at Patmo of 940 mbar etc.
- BMW M4 GT4 G82 adapt at Patmo via LT. Reference is 1000 mbar, -1 LT must be applied per -20 mbar Patmo, this means -1 LT at Patmo of 980mb, -2 LT at Patmo of 960 mbar and -3 LT at Patmo of 940 mbar. +1 LT must be applied per +20 mbar Patmo, this means + 1 LT at Patmo of 1020mbar.

Decisions taken by the SRO GT Bureau 20/09/2024