

**BALANCE OF PERFORMANCE FOR D TRACKS:**

**SACHSENRING**

These balance of performance measures are the result of the tests, research, analysis and projections performed by SRO Ltd and are the sole property of SRO Ltd. Other series promoters, race organisers and national sporting authorities cannot use all or part of them without SRO Ltd's prior written consent. Any contravention will result in a legal action.

| Make        | FIA GT3 Homologation | Model            | Min Weight kg | BOP Ballast kg | Total Weight without driver weight kg | Engine Restrictor size mm | Min RH Front mm | Min RH Rear mm | Lambda Fixed | Comments             |
|-------------|----------------------|------------------|---------------|----------------|---------------------------------------|---------------------------|-----------------|----------------|--------------|----------------------|
| Audi        | GT3-038              | R8 LMS EVO II    | 1260          | 45             | 1305                                  | 2 x 36                    | 65,5            | 128            | 0,91         |                      |
| BMW         | GT3-053              | M4 GT3           | 1265          | 25             | 1290                                  | none                      | 82,5            | 81,5           | 1,10         | Max Pboost see table |
| Ferrari     | GT3-056              | 296 GT3          | 1275          | 20             | 1295                                  | none                      | 80              | 83             | 0,90         | Max Pboost see table |
| Lamborghini | GT3-054              | Huracan GT3 EVO2 | 1250          | 80             | 1330                                  | 1 x 51                    | 70              | 128            | 0,91         |                      |
| Mercedes    | GT3-042              | AMG GT3 EVO      | 1285          | 40             | 1325                                  | 2 x 34,5                  | 81              | 87             | 0,93         |                      |
| Porsche     | GT3-055              | 911 GT3-R (992)  | 1250          | 65             | 1315                                  | 2 x 39,5                  | 96              | 120            | 0,89         |                      |

## 1. Remarks:

1.1 Additional weight must be installed in accordance with Appendix J article 257A – 2023

1.2 Technical drawings of air restrictors for NA cars are registered with FIA. Only restrictors in compliance with this registration are allowed

1.3 Use of catalytic converter compulsory

1.4 Notes on boost control :

- Values are boost pressure ratio and need to be multiplied by the ambient pressure to get the Pboost limit.
- Competitors must adjust boost pressure relative to ambient pressure at each event
- Pboost limits linear interpolation approach
- Control of Pboost strategy see further.

1.5 The SRO GT Bureau is allowed to modify any parameter required to establish the balance of performance cfr the current Regulations.

1.6 Cfr the current Regulations : Engine reference data (iA, Lambda, Fuel inj, Cam In/Out, airbox pressure drop, etc) is the one collected during BOP tests and will be used for checks.

1.7 BMW (GT3-053) M4 GT3 – Engine settings as during Official Test @ Oschersleben and datasheet date 220404 98

# Balance of Performance FIA GT3 Specification

## Pboost Ratio table for Turbo cars

| Engine speed | BMW<br>M4 GT3                  | Ferrari<br>296 GT3             |
|--------------|--------------------------------|--------------------------------|
| RPM          | Pboost ratio @ rpm @<br>Lambda | Pboost ratio @ rpm @<br>Lambda |
| 4000         | 2.330 @ 1.10                   | 1.79 @ 0.90                    |
| 4250         | 2.380 @ 1.10                   | 1.91 @ 0.90                    |
| 4500         | 2.450 @ 1.10                   | 2.13 @ 0.90                    |
| 4750         | 2.480 @ 1.10                   | 2.21 @ 0.90                    |
| 5000         | 2.540 @ 1.10                   | 2.525 @ 0.90                   |
| 5250         | 2.600 @ 1.10                   | 2.525 @ 0.90                   |
| 5500         | 2.670 @ 1.10                   | 2.515 @ 0.90                   |
| 5750         | 2.700 @ 1.10                   | 2.500 @ 0.90                   |
| 6000         | 2.730 @ 1.10                   | 2.485 @ 0.90                   |
| 6250         | 2.750 @ 1.10                   | 2.465 @ 0.90                   |
| 6500         | 2.640 @ 1.10                   | 2.445 @ 0.90                   |
| 6750         | 2.540 @ 1.10                   | 2.415 @ 0.90                   |
| 7000         | 2.400 @ 1.10                   | 2.385 @ 0.90                   |
| 7250         | 2.230 @ 1.10                   | 2.365 @ 0.90                   |
| 7500         | 2.100 @ 1.10                   | 2.345 @ 0.90                   |
| 7750         | 2.050 @ 1.10                   | 2.255 @ 0.90                   |
| 8000         | 2.000 @ 0.90                   | 2.165 @ 0.90                   |
| 8100         | 1.000 @ 0.90                   | 1.000 @ 0.90                   |

LED Boost control strategy  
V11 GT3

